



Thermal/Chloro-CatalyticOxidizer
Propane or Natural Gas
Unit# 33

Environmental Treatment Specialists



- General Specifications: 500 SCFM @20" H₂O
Scrubber System
- Trailer: 8 ft wide x 30 ft long x 9 ft height
9,000 pound double axle trailer
- Main Equipment: 3 Hp XP Blower
Flame Arrestor
Heat Exchanger
Burner (336,000 BTU/Hr)
Stainless Steel Reactor
Catalyst to treat chlorinated compounds
Scrubber system for HCl treatment
Circular Chart Recorder (inlet and Outlet Temperatures)
Completely enclosed system
Vacuum and pressure gauges, sample ports
- Trailer Specifications: System is mounted on back of flat bed trailer
- Control Panel: PLC (Program Logic Controller)
On/Off switch all components
Emergency stop button
Fault lights and reset
Interlock connections
- Inlet Hose Connection: 1 - Male camlock 6" inlet fittings (30 ft hose w/system)
Auto dilution valve
- Outlet Hose Connection: 8" air stack from top of enclosure (20 ft. high)
- Power Requirements: 240 volt, 3 phase, 100 Amp service

ProAct Services Corporation

Corp Office: 231-843-2711
Gulf Coast: 210-862-6467
or 713-202-6351
Midwest Office: 231-342-1115
East Coast Office: 203-262-1200

www.proact-usa.com

Texas • Colorado • Michigan • New Jersey • Connecticut